

Stride™ M



Driven by Tempus

T Stride M Pro, T Stride M 800, T Stride M 700, T Stride M 600, T Stride M 500
312 BTE hearing aid series



SoundCore

		T Pro	T 800	T 700	T 600	T 500	Fitting guides
SoundNav	Music	•	•				
	Noise	•	•	•			
	Conversation in a crowd	•	•	•			
	Conversation in a small group	•	•	•			
	Conversation in quiet	•	•	•	•		
	Conversation in noise	•	•	•	•		
	Quiet	•	•	•	•		
	Total environments	7	7	6	3	AutoMic	
SpeechPro	SpeechPro	•	SpeechZone2	SpeechZone			
	Speech Locator	•	•	•			
	Speech Focus	•					
	Dynamic Spatial Awareness	•					
Sound Conductor	Speech enhancement	•	•	•	•	•	
	Noise reduction	•	•	•	•	•	
	Adaptive directionality	Multiband	Multiband	Multiband	Multiband	•	
Spatial Awareness	Spatial Awareness	Dynamic	Personalized	•			
	Pinna Effect	•	•	•	•	•	

Sound Stabilization

	AntiShock 2	•	•	•	•	•	
	Wind control	•	•	•	•	•	
	Feedback manager	•	•	•	•	•	
	Natural Sound Balance	•	•	•	•	•	

Experience innovations

Patient insights	Log It All	•	•	•	•	•	
	Patient Ratings	•	•	•	•	•	
	Data logging	•	•	•	•	•	
Flex	Flex:trial	•	•	•	•	•	
	Flex:upgrade		•	•	•	•	

Convenience

	DuoLink	•	•	•	•	•	
	Telecoil and easy-t	•	•	•	•	•	
	Binaural Phone	•	•	•	•		

Fitting

	Automatic Adaptation Manager	•	•	•	•	•	
	MyMusic	Binaural	Binaural	•	•	•	
	Frequency compression	•	•	•	•	•	
	Tinnitus masker	•	•	•	•	•	
	IntelliVent	•	•	•	•	•	
	Streaming programs	•	•	•	•	•	
	Manual programs	•	•	•	•	•	
	NAL-NL2/NL1 and DSLv5	•	•	•	•	•	
	Fitting channels	20	20	16	10	6	


Stride M is rated IP 68

ANSI 3.22 2014/IEC 60118-7 2005 2cc coupler technical data

Reference test frequency - IEC 60118-7 (kHz)

1.6

1.6



OSPL90

Maximum (dB SPL)

122

129

HFA - OSPL90 (dB SPL)


112

121

at RTF (dB SPL)

108

125



Full on gain (input 50 dB SPL)

Maximum (dB)

56

63

HFA - FOG (dB)


48

53

at RTF (dB)

48

60



Reference test setting (RTS)

Frequency range (Hz)

<100 - 6500

<100 - 6500

Reference test gain (dB)

35

44

Current drain at RTS (mA)

1.3

1.4

Typical battery life (h)

140

130

Equivalent input noise at RTS (dB SPL)


19

19

Total harmonic distortion at 500 Hz/800 Hz/1600 Hz (%)

1.5/1.5/2.0

5.0/3.0/2.0



Induction coil sensitivity (31.6 mA/m)

HFA SPLTS/STS-RSETS (dB SPL/dB)

95/0

104/0

Standard: mic at 70 dB SPL vs induction coil at 100 mA/m

— Mic
- - - Induction Coil

Electromagnetic compatibility

EMC immunity by ANSI c63.19-2011 EMC, omni/telecoil

M4/T4


M4/T4

IEC 60118-0 OES coupler technical data

Reference test frequency - IEC 60118-0 (kHz)

1.6

1.6



OSPL90

Maximum (dB SPL)


126

134

at RTF (dB SPL)

116

133



Full on gain (input 50 dB SPL)

Maximum (dB)


60

68

at RTF (dB)

55

67



Basic frequency response

Frequency range (DIN 45605) (Hz)

<100 - 6600

700 - 6300

Reference test gain (dB)

41

58

Current drain at RTG (mA)

1.2

1.2

Typical battery life (h)

150

150

Equivalent input noise at RTG (dB SPL)


19

19

Total harmonic distortion at 500 Hz/800 Hz/1600 Hz (%)

1.5/1.5/2.0

8.0/5.0/2.0



Induction coil sensitivity

at RTF (graph shown for 31.6 mA/m at RTG) (dB SPL)

101

118

Electromagnetic compatibility

EMC immunity by IEC 60118-13, 2011 field strength
90/50/35 V/m, omni. IRIL low/medium/high band (dB SPL)

16/16/16

30/15/15

Legend

Test conditions

— Earhook
— Slimtubue

Earhook: filtered; Battery size: 312; Source: voltage 1.3 V; Tubing: length 25 mm, inside diameter 1.93 mm
The hearing instrument is set to Unitron Truefit test settings. LLE is applied at an approximate level of 35 dB SPL.
Domes should never be fit on patients with perforated eardrums, exposed middle ear cavities, or surgically altered ear canals. In the case of such a condition, we recommend use of a customized earmold.
Sound pressure level of these hearing aids exceeds 132 dB SPL.
We reserve the right to change specification data without notice as improvements are introduced.