





DX Insera 9 W 312 Dir, DX Insera 7 W 312 Dir, DX Insera 5 W 312 Dir, DX Insera 3 W 312 Dir In-the-ear (ITE) direct connectivity hearing instrument series

SoundCore		Discover Next 9	Discover Next 7	Discover Next 5	Discover Next 3
Environmental classification	SoundNav 3.0	•	•	•	•
	Total listening environments	7	6	4	2
	Conversation in a crowd	•			
	Conversation in a small group	•	•		
	Music	•	•		
	Quiet	•	•	•	
	Noise	•	•	•	
	Conversation in quiet	•	•	•	•
	Conversation in noise	•	•	•	•
	Total streaming environments	2	2	2	2
	MediaNav speech	•	•	•	•
	MediaNav music	•	•	•	•
Sound optimization	Sound Conductor	•	•	•	•
	Speech enhancement	•	•	•	•
	Soft speech lift	•	•	•	
	Noise reduction	•	•	•	•
	Microphone features	•	•	•	•
Localization	Spatial Awareness	•	•	•	
	Personalized	•			
	Pinna Effect	•	•	•	•
Performance in challenging environments	SpeechPro	•			
	Speech Locator	•	•		
	Speech Focus	•			
	Spatial Speech	•			
	Spectral Speech	•			
	SpeechZone 2		•		
Fine-tuning channels		20	16	14	12


Fitting guides




Moderate



Power



Super power



Ultra power

Available in all technology levels

Sound stabilization

- > AntiShock 2
- > Wind control
- > Feedback manager
- > Natural Sound Balance

Ease and convenience

- > Made For All direct connectivity
- > DuoLink
- > Binaural Phone
- > TV Connector
- > Remote Control
- > PartnerMic
- > RogerDirect
- > Remote adjust
- > Remote Plus app
 - > Equalizer

Fitting


- > First fit workflow
- > Automatic Adaptation Manager
- > Frequency compression 2
- > Tinnitus masker
- > MyMusic
- > Manual programs
- > IntelliVent

FLEX

- > FLEX:UPGRADE
- > Insights
 - > Log It All
 - > Ratings (including proactive alerts)
 - > Coach
 - > Overall satisfaction
 - > Usage


Not all technology levels are available in all markets.

ANSI 3.22 2014/IEC 60118-0: 2015 2cc coupler technical data




OSPL90

Maximum (dB SPL)	109	115	119	127
HFA - OSPL90 (dB SPL)	103	111	114	120



Full on gain (input 50 dB SPL)

Maximum (dB)	40	50	60	70
HFA - FOG (dB)	35	46	54	62



Reference test setting (RTS)

Frequency range (Hz)	<100 - 7000	<100 - 6700	<100 - 7000	<100 - 5200
Reference test gain (dB)	26	34	37	43
Current drain at RTS (mA)	2.0	2.0	2.0	2.1
Equivalent input noise at RTS (dB SPL)	19	19	19	19
Total harmonic distortion at 500 Hz/800 Hz/1600 Hz/3200 Hz (%)	1.0/1.5/1.0/1.0	1.0/1.0/1.0/1.0	1.0/1.0/1.0/1.0	1.0/1.0/1.0/1.0

Legend

Test conditions

- Ultra Power
- Super Power
- Power
- Moderate Power

Battery size: 312; Source voltage: 1.3 V; Vent: closed at canal end.
 Unless otherwise specified, all data obtained are measured with 5 mm tubing.
 The hearing instrument is set to Unitron TrueFit test settings. LLE is applied at an approximate level of 35 dB SPL.
 We reserve the right to change specification data without notice as improvements are introduced.

WARNING: Changes or modifications to the hearing aid that are not explicitly approved by the manufacturer are not permitted. Such changes may damage the ear or the hearing aid.