




# Starkey | Technical Data

## IIC NW

### Invisible-In-Canal

#### Fitting Range

- L-
- L
- M



## Signature Series 24

### Color Guide

#### Faceplate Colors



#### Shell Colors



### Patient Features

- IP Rating: 68
- Tinnitus Technology

	L-	L	M	Matrices: L-, L, M Battery Size: 10
<b>Measurement</b>	<b>ANSI/IEC 2cc Coupler</b>	<b>ANSI/IEC 2cc Coupler</b>	<b>ANSI/IEC 2cc Coupler</b>	
Peak OSPL90 (dB SPL)	110	110	115	
HFA OSPL90 (dB SPL)	104	105	110	
Peak Gain (dB)	36	41	49	
HFA Full-On Gain (dB)	30	36	46	
<b>Frequency Range (Hz)</b>	<100-9400	<100-9400	<100-8660	
HFA Frequencies (kHz)	1.0,1.6,2.5	1.0,1.6,2.5	1.0,1.6,2.5	
Reference Test Gain (dB)	27	28	33	
Equivalent Input Noise (dB) <sup>1</sup>	25	25	25	
Equivalent Input Noise (dB) <sup>2</sup>	14	14	14	
<b>Harmonic Distortion</b>				
500 Hz (%)	<3	<3	<3	
800 Hz (%)	<3	<3	<3	
1600 Hz (%)	<3	<3	<3	
<b>Estimated Battery Life for 16-Hour Day</b>				
10 Zinc Air (days)	Up to 7	Up to 7	Up to 7	
Battery Current (mA)	1.1	1.1	1.2	
<b>Tinnitus Therapy Stimulus</b>				
Max RMS Output (dB SPL)	87	87	87	
Weighted RMS Output Level (dB SPL)	87	87	87	
Max 1/3 Octave Output (dB SPL)	87	87	87	

<sup>1</sup> With expansion off

<sup>2</sup> With expansion on






# Starkey | Technical Data

## IIC NW

Invisible-In-Canal

### Signature Series 24



Latency (ms) 4.3

Attack Time (ms) 3

Release Time (ms) 60

Starkey is a trademark of Starkey Laboratories, Inc.

©2023 Starkey Laboratories, Inc. All Rights Reserved. 11/23 SPEC3077-00-EN-ST